

Wallaby Spreaders

Known for superior design, durability & cost effectiveness our range of PTO spreaders are designed to spread a large variety of materials including chicken manure, cow manure, seed, sawdust, lime, gypsum & top soil.

Our strong industry leading reputation is supported by our ability to design, manufacture & supply simple & highly efficient spreaders to hundreds of satisfied Australian customers over the past 25 years.

Why should you choose a Wal-Ag Wallaby Spreader?

- **Highly durable** – fully welded all steel construction
- **Engineered design** - fast, even spreading, elimination of spillage & blockages, wide floor to facilitate large volumes & steep sides to reduce bridging
- **Cost effective** – very competitively priced
- **Handles well in rough terrain**
- **Versatile** - will spread a large range of materials
- **Simple & easy to use** – simply attach to your tractor
- **Australian designed & manufactured** by a Newcastle based family business
- **Easy access to spare parts**
- **Superior safety inclusions**
- **Personalized service** – liaise directly with the sales & technical team
- **Customisable design** – a range of standard optional extras available or we can completely custom design spreaders for every use including feedlots, dairies, mine sites, broad acre farming, orchards & narrow vineyards
- **Well tested & refined design** - over 25 years in the Australian market
- **One year warranty & strong manufacturer support**
- **Low maintenance** – minimal lubrication required



Specifications

**4m³ & 6m³
are ideal for**

Vineyards, orchards
& all horticultural
operations

**7.70m³
is ideal for**

Vineyards, orchards,
smaller chicken
farms & all
horticultural
operations

**10m³
is ideal for**

Poultry farms, dairy
farms & general
purpose spreading

**12m³ & 16m³
are ideal for**

Small to medium
feedlots

**23m³
is ideal for**

Broadacre
applications
& large feedlots



4+6m³



7.70m³



10m³



12+16m³



23m³

SIZE	4m ³	6m ³	7.70m ³	10m ³	12m ³	16m ³	23m ³
Powered By	PTO driven hydraulic pump						
Wheels	Single or dual						
Axle	Light truck			Heavy duty truck			
Construction	Fully welded all steel construction						
Chassis	6mm steel plate						
Floor	6mm steel plate						
Bin	3mm steel plate						
Spinners	6mm steel plate						
Main Drive Shaft	50mm diameter						
Hoses	241 bar (3500 PSI)						
Conveyor Chain	Heavy duty conveyor chain. 24000 lbs tensile strength each chain.						
	Operates At			Safety Inclusions			
	41 - 55 bar (600-800 PSI) - Lightly loaded			Fully guarded secondary drive train			
	103 bar (1500 PSI) - Dry litter			Conveyor chain guards			
	172 bar (2500 PSI) - Peak permissible			Spinner guard rail			
				Tensioning system			
	Optional Extras						
	Side delivery conveyor			Spinner &/or conveyer remote speed control			
	Seed/trace element box			Mine spec tyres			
	Baffle plate			Mine spec spinner safety guards			
	Spinner shroud			Bin & conveyer discharge CCTV cameras			
	Dump valve			Bridging bar			